



At the heart of the *image*™

AF-S TELECONVERTER TC-20E III TELECONVERTER LENS

AF-S TELECONVERTER TC-20E III
TELECONVERTER LENS

FEATURES

- **Enhanced Telephoto Versatility**
Affordable and portable gateway to extend telephoto reach; ideal for sports, wildlife, surveillance and more.
- **2x Optical Conversion Factor**
Doubles the focal length of select compatible NIKKOR lenses.
- **Aspherical Lens Element**
Virtually eliminates coma and other aberrations, especially at wide apertures.
- **Nikon Integrated Coating (IC)**
Enhances light transmission efficiency, improves color consistency and reduces flare.
- **Advanced Optical Design**
7 elements in 5 groups optimized for use with FX and DX digital SLRs, engineered to meet the needs of professional photographers.



For more information visit nikonusa.com



At the heart of the *image*™

AF-S TELECONVERTER TC-20E III

TELECONVERTER LENS

SPECIFICATIONS | AF-S TELECONVERTER TC-20E III

Optical Conversion Factor	2x, effectively doubles the focal length of attached lens
Light Loss	2 f-stops
Lens Construction	7 elements in 5 groups, with one aspherical element
Compatible Formats	FX-format D-SLR, FX-format D-SLR in DX Crop Mode, DX-format, 35mm Film SLR
Dimensions (diameter x length)	Approx. 2.6 x 1.9 in. / 66 x 48mm (extension from the camera's lens-mounting flange).
Weight	Approx. 11.6 oz. / 330 g
Supplied Accessories	BF-3A front (Teleconverter) cap; LF-1 rear lens cap; CL-0715 case
NIKKOR Lens Compatibility	See TC-20E III AF-S Teleconverter—NIKKOR Lens Compatibility chart*
Product Number	2189

*For additional information about NIKKOR Teleconverter compatibility and/or functionality limitations, refer to Nikonusa.com, the documentation packaged with the NIKKOR lens and/or Teleconverter, information provided in Nikon product brochures or call Nikon Technical Support, toll-free at 800-645-6689.