



AF-S NIKKOR 200-400mm f/4G ED VR II SUPER TELEPHOTO LENS

At the heart of the *image*™

AF-S NIKKOR 200-400mm f/4G ED VR II
SUPER TELEPHOTO LENS

FEATURES

- **Versatile Super-Telephoto Zoom Lens**
Powerful super-telephoto zoom lens that's perfect for sports and wildlife shooting offering constant maximum aperture and VR II image stabilization.
- **Nikon VR II (Vibration Reduction) Image Stabilization**
Vibration Reduction, engineered specifically for each VR NIKKOR lens, enables handheld shooting at up to 4 shutter speeds slower than would otherwise be possible, assuring dramatically sharper still images and video capture.
- **Nano Crystal Coat**
Further reduces ghosting and interior flare across a wide range of wavelengths for even greater image clarity.
- **4 Extra-low Dispersion (ED) Elements**
Offers superior sharpness and color correction by effectively minimizing chromatic aberration, even at the widest aperture settings.
- **Three Focus Modes**
A/M mode joins the familiar M/A and M modes, enhancing AF control versatility with fast, secure switching between auto and manual focus to accommodate personal shooting techniques.
- **Internal Focus (IF)**
Provides fast and quiet autofocus without changing the length of the lens, retaining working distance throughout the focus range.
- **Exclusive Nikon Silent Wave Motor (SWM)**
Enables fast, accurate and quiet autofocus.
- **Nikon Super Integrated Coating (SIC)**
Enhances light transmission efficiency and offers superior color consistency and reduced flare.
- **Rugged Construction**
Featuring enhanced dust and moisture-resistance, magnesium die-cast barrel construction and a protective meniscus front lens.
- **Close Auto Focusing to 6.6 feet at all focal lengths**
Focus to 6.6 feet using AF or 6.4 feet using manual focus enabling striking image perspectives.
- **Rounded 9-Blade Diaphragm**
Renders more natural appearance of out-of-focus image areas.
- **Teleconverter Compatible**
Nikon TC-14E II, TC-17E II and TC-20E II/III Teleconverters. AF operation only with TC 14E II.



For more information visit nikonusa.com



AF-S NIKKOR 200-400mm f/4G ED VR II SUPER TELEPHOTO LENS

At the heart of the image™

SPECIFICATIONS

AF-S NIKKOR 200-400mm f/4G ED VR II

Focal Length	200-400mm
Maximum Aperture	f/4
Minimum Aperture	f/32
Lens Construction	24 elements in 17 groups
Picture Angle	12° 20' - 6° 10' (8° - 4° when used in DX Crop mode or with DX-format D-SLRs)
Minimum Focus Distance	6.6 ft./2 m (MF: 6.4 ft./1.95 m)
Maximum Reproduction Ratio	0.27x
VR (Vibration Reduction) Image Stabilization	Yes. Provides up to 4 stops of compensation
Advanced Coating	Nikon Nano Crystal Coat (N)
ED (Extra Low Dispersion) Elements	4
Focusing	Autofocus with Silent Wave Motor (SWM) and manual focus
Internal Focus (IF)	Yes
Aperture Control	Via camera Command Dial
Diaphragm Blades	9 (rounded)
Filter Attachment Size	52mm Slip-in
Dimensions (diameter x length)	(Approx.) 4.9 x 14.4 in./124 x 365.5mm
Weight	(Approx.) 118.5 oz/3,360 g
Supplied Accessories	LF-1 Rear Lens Cap; Front Cap, HK-30 Bayonet Lens Hood; CL-L2 Soft Case; 52mm Filter Holder; 52mm Nikon NC Filter
Product Number	2187