



At the heart of the *Image*™

AF-S NIKKOR 35mm f/1.4G WIDE-ANGLE LENS

AF-S NIKKOR 35mm f/1.4G
WIDE-ANGLE LENS

FEATURES

- **FX-format, ultra-fast classic wide-angle lens**
Update of one of Nikon's most respected NIKKOR lenses; suitable for landscapes, night scenes, interiors, weddings, photojournalism and astrophotography.
- **Nano Crystal Coat**
Use of Nano Crystal Coat further reduces ghosting and interior flare across a wide range of wavelengths for even greater image clarity.
- **Optimized for edge to edge sharpness on both FX and DX-format D-SLRs**
DX-format D-SLR the angle of view is equivalent to a focal length of 52.5mm in FX/35mm format.
- **Aspherical Lens Element**
Aspherical lens element virtually eliminates coma and other types of aberration, even when shooting at the widest available aperture.
- **Rear Focus (RF)**
Provides smooth and fast autofocus while eliminating front barrel rotation and lens length changes.
- **M/A Focus Mode Switch**
Enables quick changes between manual and autofocus operation. Now enhanced with a refined MF driving mechanism to reduce focus time lag and improve ease of use in M/A mode.
- **Exclusive Nikon Silent Wave Motor (SWM)**
Enables fast, accurate and quiet autofocus.
- **Nikon Super Integrated Coating (SIC)**
Enhances light transmission efficiency and offers superior color consistency and reduced flare
- **Rounded 9-Blade Diaphragm**
Renders a more natural appearance to out-of-focus image elements.





AF-S NIKKOR 35mm f/1.4G WIDE-ANGLE LENS

At the heart of the image™

SPECIFICATIONS

AF-S NIKKOR 35mm f/1.4G

Focal Length	35mm
Maximum Aperture	f/1.4
Minimum Aperture	f/16
Lens Construction	10 elements in 7 groups
Picture Angle	63° (44° when used in DX Crop mode or with DX-format D-SLRs)
Minimum Focus Distance	0.98 ft./0.30 m
Maximum Reproduction Ratio	0.2x
Advanced Coating	Nikon Nano Crystal Coat (N)
Aspherical Lens Element	1 glass element
Focusing	Autofocus with Silent Wave Motor (SWM) and manual focus
Rear Focus (RF)	Yes
Aperture Control	Via camera Command Dial
Diaphragm Blades	9 (rounded)
Filter Attachment Size	67mm Screw-on
Dimensions (diameter x length)	(Approx.) 3.27x 3.52 in. / 83 x 89.5 mm
Weight	(Approx.) 21.2 oz / 600g
Supplied Accessories	LF-4 Rear Lens Cap; LC-67mm Snap-on Front Cap, HB-59 Bayonet Lens Hood; CL-1118 Semi-Soft Case
Product Number	2198